

# Technical Datasheet

		EN ISO 13485 certified
<b>Article - No:</b>	<b>09-580-0020</b>	<b>Revision: 6</b>
<b>Remarks</b>		<b>single use only</b>

## Specification

<b>Product</b>	np GREEN SWAB, LTM-n, 3ml , 1 flocked swab (nasall) with nylon head, sterile R, breakpoint at 80mm and ABS stick, , , , tube CE/IVD, swab CE2797										
<b>Classification</b>	tube CE/IVD, swab CE2797										
<b>Dimensions</b>	<table border="1"> <tr><td>Tube:</td></tr> <tr><td>Length: 82,6 mm</td></tr> <tr><td>Diameter: 13 mm</td></tr> <tr><td>Cap Diameter: 16,6 mm</td></tr> <tr><td>Swab (rod):</td></tr> <tr><td>Length: 150 mm</td></tr> <tr><td>Diameter: 2,5 mm and 1,5 mm</td></tr> <tr><td>Tip Diameter: 2mm</td></tr> <tr><td>Tip Length: 20mm</td></tr> <tr><td>Breakpoint: 80 mm</td></tr> </table>	Tube:	Length: 82,6 mm	Diameter: 13 mm	Cap Diameter: 16,6 mm	Swab (rod):	Length: 150 mm	Diameter: 2,5 mm and 1,5 mm	Tip Diameter: 2mm	Tip Length: 20mm	Breakpoint: 80 mm
Tube:											
Length: 82,6 mm											
Diameter: 13 mm											
Cap Diameter: 16,6 mm											
Swab (rod):											
Length: 150 mm											
Diameter: 2,5 mm and 1,5 mm											
Tip Diameter: 2mm											
Tip Length: 20mm											
Breakpoint: 80 mm											
<b>Material Characteristics</b>	<table border="1"> <tr><td>tube: polypropylene (PP)</td></tr> <tr><td>tube cap: polyethylene (PE)</td></tr> <tr><td>swab: Acrylonitrile butadiene styrene (ABS)</td></tr> <tr><td>head of swab: nylon</td></tr> </table>	tube: polypropylene (PP)	tube cap: polyethylene (PE)	swab: Acrylonitrile butadiene styrene (ABS)	head of swab: nylon						
tube: polypropylene (PP)											
tube cap: polyethylene (PE)											
swab: Acrylonitrile butadiene styrene (ABS)											
head of swab: nylon											
<b>Temperature range</b>	+5 °C - +25°C										
<b>Purity Grade</b>	manufactured in clean rooms of ISO Class 8 or better (DIN EN ISO 14644-1)										
<b>Sterilisation Process</b>	radiation sterilization SAL 10-6										
<b>Shelf - Life</b>	medium: 18 months / swab: 36 months at controlled storage conditions										
<b>Packaging</b>	<table border="1"> <tr><td>pcs per inner cs: 100</td></tr> <tr><td>pcs per carton: 600</td></tr> <tr><td>pcs per pallet: 19.200</td></tr> </table>	pcs per inner cs: 100	pcs per carton: 600	pcs per pallet: 19.200							
pcs per inner cs: 100											
pcs per carton: 600											
pcs per pallet: 19.200											
<b>Storage</b>	<table border="1"> <tr><td>dry condition: 40%-60% rel. humidity</td></tr> <tr><td>inner box / cases orig. closed</td></tr> <tr><td>storage temp. +5°C to max. +25°C</td></tr> </table>	dry condition: 40%-60% rel. humidity	inner box / cases orig. closed	storage temp. +5°C to max. +25°C							
dry condition: 40%-60% rel. humidity											
inner box / cases orig. closed											
storage temp. +5°C to max. +25°C											

# Technical Datasheet

Date: 06.04.22

Page 2 of 2

pal. not stackable
--------------------

<b>Approved by nerbe plus quality department</b>
--