

Technical Datasheet

		EN ISO 13485 certified
Article - No:	09-580-3310	Revision: 6
Remarks		single use only

Specification

Product	np GREEN SWAB, Amies, 3ml , 1 flocked swab (oral) with nylon head, sterile R, breakpoint at 80mm and ABS stick, tube CE/IVD, swab CE2797										
Classification	tube CE/IVD, swab CE2797										
Dimensions	<table border="1"> <tr><td>Tube:</td></tr> <tr><td>Length: 82,6 mm</td></tr> <tr><td>Diameter: 13 mm</td></tr> <tr><td>Cap Diameter: 16,6 mm</td></tr> <tr><td>Swab (rod):</td></tr> <tr><td>Length: 151 mm (+/-0,3mm)</td></tr> <tr><td>Diameter: 2,55 mm und 1,75 mm (+/-0,15mm)</td></tr> <tr><td>Tip Diameter: 3,5 mm (+/-1,15mm)</td></tr> <tr><td>Tip Length: 16,5 mm (+4mm)</td></tr> <tr><td>Breakpoint: 80 mm</td></tr> </table>	Tube:	Length: 82,6 mm	Diameter: 13 mm	Cap Diameter: 16,6 mm	Swab (rod):	Length: 151 mm (+/-0,3mm)	Diameter: 2,55 mm und 1,75 mm (+/-0,15mm)	Tip Diameter: 3,5 mm (+/-1,15mm)	Tip Length: 16,5 mm (+4mm)	Breakpoint: 80 mm
Tube:											
Length: 82,6 mm											
Diameter: 13 mm											
Cap Diameter: 16,6 mm											
Swab (rod):											
Length: 151 mm (+/-0,3mm)											
Diameter: 2,55 mm und 1,75 mm (+/-0,15mm)											
Tip Diameter: 3,5 mm (+/-1,15mm)											
Tip Length: 16,5 mm (+4mm)											
Breakpoint: 80 mm											
Material Characteristics	<table border="1"> <tr><td>tube: polypropylene (PP)</td></tr> <tr><td>tube cap: polyethylene (PE)</td></tr> <tr><td>swab: Acrylonitrile butadiene styrene (ABS)</td></tr> <tr><td>head of swab: nylon</td></tr> </table>	tube: polypropylene (PP)	tube cap: polyethylene (PE)	swab: Acrylonitrile butadiene styrene (ABS)	head of swab: nylon						
tube: polypropylene (PP)											
tube cap: polyethylene (PE)											
swab: Acrylonitrile butadiene styrene (ABS)											
head of swab: nylon											
Temperature range	+5 °C - +25°C										
Purity Grade	manufactured in clean rooms of ISO Class 8 or better (DIN EN ISO 14644-1)										
Sterilisation Process	radiation sterilization SAL 10-6										
Shelf - Life	medium: 30 months / swab: 36 months at controlled storage conditions										
Packaging	<table border="1"> <tr><td>pcs per inner cs: 100</td></tr> <tr><td>pcs per carton: 600</td></tr> <tr><td>pcs per pallet: 19.200</td></tr> </table>	pcs per inner cs: 100	pcs per carton: 600	pcs per pallet: 19.200							
pcs per inner cs: 100											
pcs per carton: 600											
pcs per pallet: 19.200											
Storage	<table border="1"> <tr><td>dry condition: 40%-60% rel. humidity</td></tr> <tr><td>inner box / cases orig. closed</td></tr> <tr><td>storage temp. +5°C to max. +25°C</td></tr> </table>	dry condition: 40%-60% rel. humidity	inner box / cases orig. closed	storage temp. +5°C to max. +25°C							
dry condition: 40%-60% rel. humidity											
inner box / cases orig. closed											
storage temp. +5°C to max. +25°C											

Technical Datasheet

Date: 14.06.22

Page 2 of 2

pal. not stackable

Approved by nerbe plus quality department
--