

# Technical Datasheet

		EN ISO 13485 certified
<b>Article - No:</b>	<b>11-462-6000</b>	<b>Revision: 9</b>
<b>Remarks</b>	<b>max. volume: 185 ml / working volume: 170 ml</b>	<b>single use only</b>

## Specification

<b>Product</b>	Screw cap container PP, 170 ml, Ø58X99,5 mm, cap pre-assembled, container transparent, cap green, grading 3 sided, every 10ml, sterile EO
<b>Colour</b>	container transparent, cap green
<b>Graduation</b>	grading 3 sided, every 10ml
<b>Nominal Capacity</b>	170 ml
<b>Material Characteristics</b>	container: polypropylene (PP) cap: high-density polyethylene (HDPE)
<b>Temperature range</b>	-40°C - 120°C
<b>Product Characteristics</b>	leak proof of not less than 95 KPa (0,95 bar, 14 psi) biologically inert physiologically harmless no heavy metals according to EC/94/62
<b>Purity Grade</b>	do not contain any pyrogens
<b>Sterilisation Process</b>	gas sterilisation by ethyleneoxid, 10-6
<b>Shelf - Life</b>	36 months at controlled storage conditions
<b>Packaging</b>	pcs per bag: 110 pcs per carton: 110 pcs per pallet: 3.520
<b>Storage</b>	dry condition: 40%-60% rel. humidity bags / cases orig. closed storage temp. +2°C to max. +30°C pal. not stackable
<b>Approved by nerbe plus quality department</b>	

